

PM-906/PM-912 8x4 Matrix Mixer Amplifier with Paging/USB/Bluetooth

Product ID: PM-906/PM-912



Short Description

Rated power: 4x60W/4x120W

Combined with paging, USB and bluetooth

3 MIC input, 5 AUX input, 4 AUX output

Description

? Rated power: 4x60W/4x120W, 100V/70V/4-16?

? Matrix PA Amplifier combined with paging, USB and bluetooth

? 3 MIC input, 5 AUX line input, 4 AUX line output for link

? 8x4 Matrix 100V output with individual volume control output, all sound sources have the function of matrix 4-channel output

? 4 remote paging microphone interface (should work together with our CM12 remote paging microphone)

? TEL input available, with monitor speaker output

? With one key touch EMC function

? Input priority level (default):

Level 1: AUX1, Siren, TEL, remote paging, Bell

Level 2: MP3, AUX2, 3, 4, 5
 ? LED indicator, level indicator and protection indicator

Specification

Model	PM-906	PM-912
Output power	60W*4	120W*4
Output	100V, 70V, 4-16? (balanced)	
Input sensitivity	AUX (MIC) 1, 2, 3: 3.0±0.5mV/600?; 300±50mV/10K? balanced	
	AUX 4, 5: 300±50mV/10K?, unbalanced	
	Call station 1, 2: 2000±100mV/10K?, balanced	
	TEL: 300±50mV/10K?	
Frequency response	80Hz~16KHz	
T.H.D.	Less than 1% at 1KHz	
Tune control	±10dB (Bass: 100Hz); ±10dB (Treble: 10KHz)	
S/N	?55dB	
AUX line output	2V/600?, balanced	
MP3 support	MP3, WMA, WAV, ACC, 32G flash disk or by bluetooth	
Protection	Overload, short circuit, overheat, DC output	
Power requirement	AC 220~240 V / 50~60 Hz	
Net weight(Kg)	25.5	28
Gross weight(Kg)	28	30.5
Dimensions(mm)	483x440x132	
Packing dimension (mm)	550x550x215	

Product Gallery

