

L-VCM6A/EN Honeywell 6W 6.5" Fireproof Metal Ceiling Speaker EN54-24

Product ID: L-VCM6A/EN (LSC-606)

Short Description

Rated power: 6W

Speaker unit: 6.5"

Comply with EN54-24 standard

Description

- ? Comply with EN54-24 requirements
- ? With fire dome to protect wire connection
- ? Fireproof plastic wire joint and ceramic terminal
- ? High-class steel and form by stamping
- ? Aluminum grille, stainless and durable
- ? Clip type flush mount design for easy installation
- ? Equipped with steel hanging line, double ensure

Specification

Model		L-VCM6A/EN (LSC-606)
Rated/Max power		6W/9W
Power taps	100V	6/3/1.5/0.75W
	70V	3/1.5/0.75/0.375W
Line input voltage		100V/70V
Rated impedance		1.7k~/3.3k~/6.7k~/13k?
Sensitivity at rated power /1W	100 Hz-10k Hz, 1m	99dB/91d
	100 Hz-10k Hz, 4m	87dB/79dB
Frequency response (-10dB)		170-20KHz
Dispersion angle (1kHz/-6dB)		170°
Connection		Ceramic Terminal

Dimension (mm)	222x129
Hole for mounting (mm)	196
Speaker driver unit	full range 6.5"
Material	Iron
Grill color	White (RAL 9003)
Dome color	Red (RAL 3000)
Weight (Kg)	1.57

Product Gallery

