

PB-8360/PB-8460/PB-8660 Big Power Amplifier

Product ID: PB-8360/PB-8460/PB-8660



Short Description

Rated output power: 350W/450W/650W
100V/70V and 4~16? speaker output

Description

? Speaker outputs: 100V, 70V and 4~16?

? 5 LED indicators for status display

? XLR socket and 6.35 mm jack for amplifier link

? Short circuit output protection & LED display

? Series amplifiers with high output power available

Specification

Model		PB-8360	PB-8460	PB-8660
Rated output power		350W	450W	650W
Impedance	Low impedance	4-16?		
	70V	13.6?	10.7?	7.4?
	100V	27.8?	21.7?	15.1?

Line input sensitivity	10k Ω < 1V, unbalanced		
Line output	10k Ω 0.775V (0 dB), unbalanced		
S/N	>70dB		
Frequency response	60 Hz ~ 15k Hz (\pm 3dB)		
THD	<0.5% at 1kHz, 1/3 of rated power		
Damping factor	200		
Slew rate	15V/uS		
Output regulation	<3dB, from level without signal to be loaded fully		
Controls	Volume control, power switch		
Cooling style	12V DC fan		
Indicators	POWER: green CLIP: red SIGNAL: green PROT: red TEMP: orange		
Protection	AC FUSE \times 10A	AC FUSE \times 12A	AC FUSE \times 15A
	AC FUSE \times 1, short circuit, overload, high temperature		
Power Requirements	AC110V 120V, AC220V ~240V 50-60Hz optional		
Power Cord	(3 \times 1.5 mm) \times 1.5M (Standard)		
Power Consumption	485W	620W	880W
Gross Weight (Kg)	15.12	17.66	19.74
Net Weight (Kg)	16.76	19.30	21.36
Product Dimension (mm)	89(H) \times 483(W) \times 366(D)		
Packing Dimension (mm)	185(H) \times 520(W) \times 435(D)		

Product Gallery

