

EF-804 8x4 Channel Pre Amplifier with Remote Paging

Product ID: EF-804



Short Description

4 CH line output for amplifiers
4 MIC input, 4 line input
With remote paging MIC input

Description

- ? 4 Channel line output for amplifiers
- ? 4 XLR Balanced jack and 1/4" phone jack for CH1-4 input
- 4 1/4" phone jack and RCA jack for CH5-8 input
- ? 8 Gain control for each input
- ? Output Level control with 2 tone control and mute switch
- ? With remote paging MIC input (RJ45 interface)
- ? Talkover switch for Ch1
- ? Phantom Power switches for CH1 and CH2-4
- ? LED indicators: Power, SIG, CLIP for each input channel
- SIG, -20dB, -10dB, 0dB, CLIP for each output channel

Specification

Model		EF-804
Output Level / Impedance		0dB / 600 ? Balanced
Input sensitivity /Impedance	Mic Input	-50dB~ -6dB / 20K? Balanced
	Line Input	-30dB~ +14dB / 20K? Balanced
	Remote Input	0dB / 600? balanced
Frequency Response (± 1 dB)		20Hz - 20kHz
T.H.D		<0.1%
Closstalk		>70dB
Channel Quantity		4 CH
Equalization	Input	High : 12 kHz \pm 15 dB Mid : 2.5 kHz \pm 15 dB Low : 80 Hz \pm 15 dB
	Output	High : 10 kHz \pm 15 dB Low : 100 Hz \pm 15 dB
S/N Ratio		>90dB
Power Source		AC 100-240 V, 50/60Hz
Net Weight (Kg)		9.0
Dimensions (mm)		420W x 88H x 320D

Product Gallery

