

L-VBM20A/EN Honeywell 20W Aluminum Bidirectional Projection Loudspeaker

Product ID: L-VBM20A/EN



Short Description

Rated power: 20W (10Wx2)

Meets outdoor requirements

EN54-24 certified, IP65 standard

Description

L-VBM20A/EN is a high-performance 20W voice alarm bidirectional projection loudspeaker. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high-quality sound reproduction. It can be used in indoor, outdoor, dry, or wet applications, providing

reliable operations over wide temperature and humidity ranges. Bidirectional loudspeaker is the best choice for applications such as tunnel, gallery and shopping arcade. This voice alarm bidirectional projection loudspeaker complies with BS 5859 part 8 and EN54 part 24.

? Intelligible voice and superior sound reproduction

? Ceiling or wall mount

? Meet virtually any outdoor requirements

- ? EN54-24 certified
- ? Complies with IP65 standard
- ? Available with or without capacitor (part number without “C”)

Specification

| | | |
|------------------------------------|----------------------------|-------------|
| Model | L-VBM20A/EN (C) | L-VBM20A/EN |
| Max power | 30W | |
| Rated power | 20W (10Wx 2) | |
| Power taps @ 100V | 20W / 10W / 5W / 2.5W | |
| SPL at 20W / 1W (100 Hz-10 Khz,1m) | 99dB / 87dB | |
| SPL at 20W / 1W (100 Hz-10 Khz,4m) | 87dB / 75dB | |
| Frequency response(-10dB) | 150 Hz - 20 KHz | |
| Rated input voltage | 100 V / 70 V | |
| Rated impedance | 500 ? / 1K ? / 2K ? / 4K ? | |
| Connection | Fire-resistant Cable | |
| Dimensions (D x L) | ?140 mm x195 mm | |
| Weight | 3.23 Kg | |
| Color | White (RAL9003) | |
| Material | Aluminum | |
| DC Blocking Capacitor | Yes (2.7uF) | No |

Product Gallery

