
#### Phone: +86-20-39390663 - Email: sales@lyintl.com

# HS-3404/HS-3504/HS-3604 Outdoor All Weather Waterproof Ceiling Hanging Pendant Speaker





### **Short Description**

Rated power: 20W/30W/40W Line input: 70V/100V/8?

 $4''/5.25''/6\frac{1}{2}''$  woofer + silk tweeter

IP66 All weatherproof

### **Description**

Combination design and great sound wall mounted speaker, with the high-class woofer, bring users outstanding sound quality. High temperature resistance and IP66 weatherproof, can be used in indoor and outdoor. With the special brackets, the speaker can be easily mounted under various angles in corners or on surfaces such as wall and ceiling.



# High quality 2-way coaxial PP woofer & silk tweeter



Powder-coated Rust-resistant Grille

Matte surface





 $70V/100V/8\Omega$  inputs With multi power taps

Suitable for home and commercial usage

- ? 3 mounting method: wall-mounted, floor-stand and pendant type
- ? Build-in 70V/100V transformer and 8? power taps
- ?  $1\times4$ ",  $1\times5.25$ " or  $1\times6\frac{1}{2}$ " PP woofer speaker driver and silk tweeter
- ? Rated output power: 20W, 30W or 40W
- ? IP66 all weatherproof, suitable for indoor and outdoor use

# ? White and black color for option





# Specification

Model	HS-3404	HS-3504	HS-3604
Rated power	20W	30W	40W
Power taps	2.5/5/10/20W/0/8?	3.7/7.5/15/30W/0/8?	5/10/20/40W/0/8?
Output SPL	83±3dB	84±3dB	85±3dB
Freq. Response	129Hz~20KHz	118Hz~20KHz	100Hz~20KHz
LF Unit	4" graphite cone	5.25" graphite cone	6½" graphite cone
HF Driver	0.75"x1 silk dome	1"x1 silk dome	1"x1 silk dome
Waterproof	IP66	IP66	IP66
Dimension	190x138x138	240x170x170	280x208x208
(H*W*D) (mm)			
Net Weight (Kg)	1.63	2.4	3.01
Gross Weight (Kg)	5.6 (2pcs)	6.35 (2pcs)	7.66 (2pcs)
Packing Dimension	500x300x270	510x360x270	520x420x270
(L*W*H) (mm)			

### **Product Gallery**





