

LS-D25TH/LS-D26TH 5"/6.5" Coaxial Frameless In-Ceiling Speaker with Fireproof Dome

Product ID: LS-D25TH/LS-D26TH



Short Description

Rated power: 30W or 40W

Line input: 100V

Speaker driver: 5" or 6.5" woofer + ¾" tweeter

Frameless magnetic grille

Description

Fashion design **Frameless magnetic grille**.

This series indoor ceiling speaker is coming with 5" or 6.5" woofer speaker driver and a 0.75" tweeter driver, 100 input.

Power taps:

LS-D25TH: 30W/100V (5"+0.75")

LS-D26TH: 40W/100V (6.5"+0.75")

High-class ABS material frame and metal fireproof dome.

Suitable for public address system background music and home theater audio system usage.

Specification

Model	LS-D25TH	LS-D26TH
Rated power	30W	40W
Max power	60W	80W
Power taps (100V)	-	-
Power taps (70V)	-	-
Line input	100V	
Sensitivity (1m,1W)	90±3dB	92±3dB
Frequency response	120-16KHz	300-8KHz
Woofer speaker driver	5"	6.5"
Tweeter speaker driver	¾"	
Product dimension (mm)	210x180	245x225
Hole for mounting (mm)	190	232
Frame material	ABS	
Grille material	Powder coated Iron mesh	
Rear cover material	Steel	
Color	White & Black	
Product net weight (Kg)	2.2	2.9
Gross weight (Kg)	15.0 (6pcs)	7.5(2pcs)
Packing dimension (cm)	54x27x34	65x33x37

Product Gallery

